


GHM9-63 Miniature Circuit Breaker



	Standard		IEC/EN 60898-1
Electrical features	Rated current In	A	2,4,6,10,16,20,25,32,40,50,63
	Poles	P	1,2,3,4
	Rated voltage Ue	V	AC 240/415
	Insulation voltage Ui	V	500
	Rated frequency	Hz	50/60
	Rated breaking capacity	A	3000, 4500 (2~40A/6000)
	Rated impulse withstand voltage(1.2/50) Uimp	V	4000
	Dielectric test voltage at ind. Freq. for 1min	kV	2
	Pollution degree		2
	Thermo-magnetic release characteristic		B, C, D
Mechanical features	Electrical life	t	4000
	Mechanical life	t	10000
	Protection degree		IP20
	Reference temperature for setting of thermal element	℃	30
	Ambient temperature (with daily average ≤35℃)	℃	-5~+40(Special application please refer to temperature compensation correction)
	Storage temperature	℃	-25~+70
Installation	Terminal connection type		Pin-type busbar
	Terminal size top / bottom for cable	mm ²	25
		AWG	18-3
	Terminal size top / bottom for busbar	mm ²	25
		AWG	18-3
	Tightening torque	N*m	2
		In-lbs.	18
	Mounting		On DIN rail EN 60715(35mm) by means of fast clip device
	Connection		From top and bottom



Wiring Diagram



Overall and mounting dimensions(mm)

