Hydraulic Tools



HT-300

KYQ-300B

Hydraulic crimping pliers HT-300 type

- * crimping of aluminum or copper donductors with cable terminals or bush in the corresponding size
- * crimping head turning at 360oC which facilitates the crimping of static conductors.
- * device for automatic following of the effort at crimping completion.
- * from of the crimping elemeth:hexahedral
- * size of the crimping element:16,25,35,50,70,95,120,150,185,240,300 mm2
- * section of the crimping conductors:

- Al conductors-from 16 to 300 mm2

- Cu conductors-from 16 to 240 mm2

- * element pressing power:60kN
- * width of the element:17mm
- * length: 460mm * used hydraulic oil:shell tellus T15
- * A set of congestion hoops for the hydraulic cylinder
- - Functions:

* Crimping of aluminum or cooper conductors with cable terminals or bush in the corresponding size.

Technical data:

* form of the crimping element:hexahedral

- * section of the crimping conductors:
- al conductors-from 16 to 300 mm2
- * Element pressing power:16T
- * Used hydraulic oil:#23(hydraulic oil with viscosity 23)

* Length:500mm

- * A set of congestion hoops for the hydraulic cylinder
- Hydraulic crimping pliers YQK-300 type
- Functions:

YQK-300

YQK-70

WK-8

SYK - 15

All conductors-from 16 to 300 mm2

- * Element pressing power:16T
- * Length:500mm

* Used hydraulic oil:shell tellus T15

- * A set of congestion hoops for the hydraulic cylinder

Hydraulic crimping pliers YQK-70 type

- * Crimping of aluminum or copper conductors with cable terminals or bush in the corresponding size Technical data:
- * Section of the crimping conductors:
- Cu conductors-from 4 to 70mm2
- * Length:310mm

* Metal box for the instrument

HYDRAULIC PIERCING INSTRUMENTS

* A set of congestion hoops for the hydraulic cylinder

Hydraulic piercing pliers WK-8 type Functions

* Piercing head turning at 360o

* Form of the curring element:round

* Cutting through openings in sheet metal with gauge up to 3mm without rotary motion.

 sheet metal 3mm - openings up to φ30mm - sheet metal 2mm - openings up to φ60mm

* Element pressing power:80kN

- * Thickness of the element: 25mm * Weight of the instrument: 3.5kg
- * Metal box for the instrument
- * Additional set of cutting elements for cable glands-φ16,20,26.2,32.5,39,51,63 and a square for display devices 46.5 × 46.5,68 × 68(ordered additionally)

* Used hydraulic oil:#15(hydraulic oil with viscosity 15)

Functions: * Cutting through openings in sheet metal with gauge up to 3mm without rotary motion.

* Proctracting piercing head supplied with a hose for the hydraulic oil that gives possibility for piercing openings everywhere on the metal surface

* Form of the cutting element:

- square

-round

-round openings: O 22,27.5,34.3,40,49,60.8mm

square:32×32mm

sheet metal 3mm - openings up to φ60.8mm

* Size of the cutting elemet:

- sheet metal 2mm openings uo to φ115.5mm
- * Element pressing power:15T
- * Thickness of the element: 25mm * Weight of the element:11.5kg
- * Metal box for the instrument
- Additional set of cutting elements for cable glands-φ16,20,26.2,32.5,39,51,63 and a square for

- * metal box for the instrument
- Hydraulic crimping pliers KYQ-300B type

* Device for automatic following of the effort at crimping completion

- Size of the crimping element:16,25,35,50,70,95,120,150,185,240,300 mm2
- cu conductors-from 16 to 240 mm2
- * Weight of the instrument: 6.8kg
- * Metal box for the instrument
- * Crimping of aluminum or copper conductors with cable terminal or bush in the corresponding size

Technical data: * Form of the crimping element:hexahedral

- * section of the crimping conductors:
- Cu conductors-from 16 to 240 mm2

* Size of the crimping element:16,25,35,50,70,95,120,150,185,240,300 mm2

- * Weight of the instrument: 6.3kg
- * Metal box for the instrument
- Functions:
- * Form of the crimping element:hexahedral Size of the crimping element: 4,6,10,16,25,35,50,70mm2.
- All conductors-from 4 to 70mm2
- * Width of the element:10mm

* Weight of the instrument: 2.8kg

* Element pressing power:8T

- * Used hydraulic oil:shell tellus T15

Technical data:

- * Size of the cutting element: φ22,27.5,34.3,40,49,60.8mm * Piercing capacity:
- * A set of congestion hoops for the hydraulic cylinder
- Hydraulic piercing press SYK-15 type
- Technical data:
- * Piercing capacity:
- square opening uo to 110×110mm
- * Used hydraulic oil:#15(hydraulic oil with viscosity 15)
- * A set of congestion hoops for the hydraulic cylinder
- display devices 46.5 × 46.5,68 × 68(ordered additionally)

Technical data:

* weight of the instrument:3.3kg

- Functions: